

Original post set 1820 by Hendricks with witnesses: 8" elm S 33 E 8 links, 7" beech N 4 W 12 links per Marion County Atlas pg. 15. Survey by D.B. Hosbrook 5-20-1850 indicates no stone but witnesses: 24" beech S 47 1/2 W 24 links, 20" hickory N 23 E 44 links per Warren Township Legal Survey Book pg. 12. Monroe 11-25-55 called a pipe over stone. Burres 8-9-63 called a pipe over stone. 3-15-66 MCSO called a brass plug. Day 11-13-69 called brass plug in concrete monument. Fortner 3-21-75 called a brass plug. Wilcoxen 7-15-88 called a brass plug with cut 'x'. Wilcoxen 10-16-96 called a mag nail set over brass plug. Excavated 6-23-99 by Wilcoxen and mag nail was found 2 1/2" down. A brass plug in concrete was found 7" down. No stone was found during excavation. Harrison was set. Re-tied 6-23-99 by Wilcoxen.

HC652701

REF.	DISTANCE	DESCRIPTION
1.	105.041	Mag nail w/brass washer E PwP#41-451E 24"up
2.	7.0.87	Cut 'x' W-bolt aluminum pole
3,	164.38′	Mag nail w/brass washer N PwP#333-451E 24"up
4.	61.89'	Mag nail w/brass washer SW PwP#10-451E 36'up
5.	81,21′	Cut 'x' W-bolt aluminum pole
6.	93.591	Top nut of fire hydrant
7.	82.10'	Cut 'x' N-bolt aluminum pole
8.	113.57'	Mag nail w/brass washer SE PwP#19-451B 30'up
9.	58,44′	Cut 'x' E-bolt aluminum pole
10.	110.74′	NE corner of brick
11.	167.45'	Mag nail w/brass washer E PwP no # 20"up